



Justrite Safety Group

417 Bubble Sof-Tred™

Dyna-Shield™ layer with unique bubble design



Ergonomic, Anti-fatigue & Safety Matting - Dry Areas Linear Lengths 417 Bubble Sof-Tred™

Exceptional worker comfort due to 12.7 mm thick specially formulated compound. Protective layer of exclusive Dyna-Shield™ extends service life by 50% compared to regular microcellular vinyl.

- Available with yellow borders along sides to comply with OSHA code 1910-144
- All 4 sides are bevelled and sealed to minimize tripping hazards
- Unique bubble design provides exceptional comfort

Recommended use



- Dry Areas
- For placement in manufacturing plants, assembly lines, picking, packing and logistics warehouses, individual work stations.
- Medium duty

Colors:

- Black/Yellow
- Grey

Sizes:

- 60cm x 91cm
- 91cm x 150cm
- 122cm x linm
- 60cm x linm
- 91cm x linm
- 122cm x 18.3m
- 60cm x 18.3m
- 91cm x 18.3m



Ergonomic, Anti-fatigue & Safety Matting - Dry Areas Linear Lengths Bubble Sof-Tred™

General

Brand	Notrax®
Category	Dry Areas Linear Lengths
Product Number	417
Product Family	Industrial & Commercial Matting
Product Group	Ergonomic, Anti-fatigue & Safety Matting
Product Name	Bubble Sof-Tred™
Recommended use	For placement in manufacturing plants, assembly lines, picking, packing and logistics warehouses, individual work stations.
Shipping Location	Barendrecht 2992SB, The Netherlands, Moselle, MS 39459
Type	Dry Areas - Dyna Shield™
Usage Intensity	Medium duty

Sustainability

Reach	Reach compliant (Registration, Evaluation, Authorization and Restriction of Chemicals).
Sustainability	Recyclable material
Warranty	3

Tests

Abrasion Resistance 1000	1.7%
Abrasion Resistance 500	0.6%
Compression Deflection 1.4	0.70 cm
Compression Deflection 2.8	0.81 cm
Elongation	140.8%
Fire rating US	Pass
Foam Battery	40 lb/in ²
Hardness	20 Shore A
Slip Rating	R10
Coefficient Friction Dry	1.10
Surface Flammability	Pass
Tear Strength	13 lb

Technical Specifications

Application	Industrial
Backing	Microcellular vinyl
Breaking Load	24.4 lb
Edges	Bevelled edges on all sides
Material	Microcellular vinyl
Material Group	Vinyl
Process	Foaming

Bubble Sof-Tred™ Grey

Art. nr.	Dimension (cm)	Weight (kg)	Thickness (mm)
417S0035GY	91cm x 150cm	5.3	12.7
417S0023GY	60cm x 91cm	2.1	12.7
417C0036GY	91cm x linm	3.5	12.7
417C0048GY	122cm x linm	4.7	12.7
417C0024GY	60cm x linm	2.3	12.7
417R0024GY	60cm x 18.3m	43	12.7
417R0036GY	91cm x 18.3m	64	12.7
417R0048GY	122cm x 18.3m	86	12.7

Bubble Sof-Tred™ Black/Yellow

Art. nr.	Dimension (cm)	Weight (kg)	Thickness (mm)
417S0035BY	91cm x 150cm	5.3	12.7
417C0048BY	122cm x linm	4.7	12.7
417C0036BY	91cm x linm	3.5	12.7
417C0024BY	60cm x linm	2.3	12.7
417S0023BY	60cm x 91cm	2.1	12.7
417R0024BY	60cm x 18.3m	43	12.7
417R0048BY	122cm x 18.3m	86	12.7
417R0036BY	91cm x 18.3m	64	12.7