




Justrite Safety Group

656S Cushion Ease Solid™ Nitrile

Heavy duty modular rubber tiles



Ergonomic, Anti-fatigue & Safety Matting - Dry Areas Modular Matting 656S Cushion Ease Solid™ Nitrile

Ergonomic benefit derived from a 19 mm thick worker platform with a closed anti-slip pebble structure surface for maximum anti-fatigue comfort in dry industrial environments.

- Heavy duty rubber tiles can be easily assembled for coverage of large areas or individual workstations, wall-to-wall or as islands
- Resistant to most industrial oils
- Compatible with patented MD Ramp System™ for smart safety bevelling solutions; allows outside and inside corners

Recommended use

- Wet/Dry and Oily Areas
- For placement in manufacturing plants, production lines, assembly lines, CNC machines, metal working for individual workstations and custom work platforms
- Heavy duty

Colors:

- Black

Sizes:

- 91cm x 91cm
- per m2

Accessories:

- 551 MD Ramp System™ Nitrile
- 552 MD-X Ramp System™ Nitrile



Ergonomic, Anti-fatigue & Safety Matting - Dry Areas Modular Matting Cushion Ease Solid™ Nitrile

General

Brand	Notrax®
Category	Dry Areas Modular Matting
Product Number	656S
Product Family	Industrial & Commercial Matting
Product Group	Ergonomic, Anti-fatigue & Safety Matting
Product Name	Cushion Ease Solid™ Nitrile
Recommended use	For placement in manufacturing plants, production lines, assembly lines, CNC machines, metal working for individual workstations and custom work platforms
Series	Cushion-Ease®
Shipping Location	Chicago, IL 60638, Barendrecht 2992SB, The Netherlands
Type	Dry Areas - Heavy Duty Modular Rubber Mats
Usage Intensity	Heavy duty

Sustainability

Reach	Reach compliant (Registration, Evaluation, Authorization and Restriction of Chemicals).
Sustainability	Recyclable material
Warranty	7

Tests

Abrasion Resistance 1000	1.50% weight loss (5000 cycles)
Compression Deflection 1.4	37.0 lb/in ² (at 25%)
Compression Deflection 2.8	98.9 lb/in ² (at 50%)
Fire rating US	Pass
Hardness	64 Shore A
Slip Rating	R9
Coefficient Friction Dry	0.88
Surface Flammability	Pass

Technical Specifications

Application	Industrial Environments
Edges	Attachable bevelled edges are available
Material	100% Nitrile rubber
Material Group	Nitrile rubber
Process	Compression Moulding

Cushion Ease Solid™ Nitrile Black

Art. nr.	Dimension (cm)	Weight (kg)	Thickness (mm)
656S0000BL	per m2	13.6	19
656S0033BL	91cm x 91cm	12	19

Accessories

551 MD Ramp System™ Nitrile 552 MD-X Ramp System™ Nitrile

