



Justrite Safety Group

830 Switchboard Matting™ Class 2

Class 2 insulation matting



Ergonomic, Anti-fatigue & Safety Matting - Switchboard Matting

830 Switchboard Matting™ Class 2

Insulating matting prevents workers from being “grounded” and provides safety in case of electrical shock. The corrugated saw-tooth top surface increases traction and is easy to sweep clean.

- Each square inch of matting is tested in conformance with ANSI/ASTM D-178 specifications
- The corrugated saw-tooth top surface increases traction and is easy to sweep clean
- Recommended maximum usage: 17,000 Volts.
- Must be replaced every 12 months for optimum safety

Recommended use

- Dry Areas
- Around electric sub-stations, transformers and switches, electrical panels, engine and generator rooms
- Heavy duty

Colors:

- Black

Sizes:

- 90cm x 150cm
- 91cm x 11m
- 91cm x 22.8m



Ergonomic, Anti-fatigue & Safety Matting - Switchboard Matting

Switchboard Matting™ Class 2

General

Brand	Notrax®
Category	Switchboard Matting
Product Number	830
Product Family	Industrial & Commercial Matting
Product Group	Ergonomic, Anti-fatigue & Safety Matting
Product Name	Switchboard Matting™ Class 2
Recommended use	Around electric sub-stations, transformers and switches, electrical panels, engine and generator rooms
Shipping Location	Barendrecht 2992SB, The Netherlands, Moselle, MS 39459
Type	Industrial Specialties - Electrical Protective Matting
Usage Intensity	Heavy duty

Sustainability

Reach	Reach compliant (Registration, Evaluation, Authorization and Restriction of Chemicals).
-------	---

Tests

Elongation	317%
Hardness	91 Shore A
Surface Flammability	Pass
Tear Strength	2505 PI

Technical Specifications

Application	Dry industrial environments
Edges	No borders
Material	PVC (DOP free)
Material Group	PVC
Process	Calendering

Switchboard Matting™ Class 2 Black

Art. nr.	Dimension (cm)	Weight (kg)	Thickness (mm)
830S0035BL	90cm x 150cm	11.6	6.4
830R0375BL	91cm x 22.8m	174	6.4
830C0036BL	91cm x linm	7.6	6.4