



Justrite Safety Group

Product Specification Sheet

Product Name: **Home Park-It® Parking Curb**

Manufacturer: NoTrax®, Justrite Safety Group/GNR
5655 West 73rd St.
Bedford Park, IL 60638
Tel.: (800) 621-2802, Fax: (800) 322-7105

Product Description: The nominal width and height of the Home Park-It® parking curb are 6 inches and 4 inches respectively. The nominal length is 22 inches. The nominal weight is 10 pounds.

The rubber parking curb is outfitted with molded in reflective yellow tape for increased visibility.

Product Specifications:

1. Material: compression molded composite of recycled rubber and polyurethane binder.
2. Physical properties of the rubber composite:

a) Density	1.04 g/cu. cm	(ASTM C642)
b) Durometer Hardness	65A ± 7	(ASTM D2240)
c) Minimum Tensile Strength*	1.4 MPa	(ASTM D412)
(* main structural areas)		
d) Compression deformation	10% at 0.5 MPa, 68°F	(ASTM D575)
e) Brittleness at Low temperature:	-40°F	(ASTM D746)
f) Freeze and thaw when exposed to deicing chemicals	no loss after 50 cycles	(ASTM C672)
g) Coefficient of thermal expansion:	14.4 x10 ⁻⁵ m/m/°C	(ASTM C531)
h) Weathering 70 hours at 158°F		(ASTM D573)
- hardness retained	100% (± 5%)	
- compressive strength	100% (± 5%)	
- tensile strength	100% (± 5%)	
- elongation retained	100% (± 5%)	
3. Dimensions:

width:	6 inches (+/- 0.11 inches)	152mm (+/- 3mm)
height:	4 inches (+/- 0.11 inches)	102mm (+/- 3mm)
length:	22 inches (+/- 0.19 inches)	559 mm (+/- 5mm)
4. Finishing: Black with molded in yellow durable reflective tape
5. Product contains: 95% of post- consumer materials and 5% of pre-consumer materials



Justrite Safety Group

Installation Method:

In most cases the Home Park-It® does not require any installation. It is designed to be placed on the floor to indicate parking position on a vehicle inside a garage.

If necessary, the Home Park-It® can be installed with two 14 inches long spikes or two 0.5 inch (12.5mm) lag bolts 6 inch (153mm) long with plastic shields.

For installation with spikes the 0.5 inch (12.5mm) diameter holes are drilled through the holes in the product into a paved road than the spikes are hammered in.

For installation with lag bolts pilot holes 0.5 inch (12.5mm) are drilled through the product installation holes. The holes are re-drilled for a size required by the shields and the shields are installed. The product is then repositioned over the mounting holes and bolted down.

Warranty:

A three (3) years warranty is provided on the rubber composite and 1 year on the reflective tape if the product is installed as per manufacturer's installation instructions.

The rubber parking curbs are intended to be used for indoor or outdoor parking lots. Any other applications could be considered outside manufacturer warranty.

Please verify with the distributor or the manufacturer if the intended installation location is covered by warranty of the product.

Any warranty claims will be assessed by the product manufacturer after adequate information is provided.

Rev. Jan. 2021